

Package: ggmap (via r-universe)

August 25, 2024

Version 4.0.0.900

Title Spatial Visualization with ggplot2

Description A collection of functions to visualize spatial data and models on top of static maps from various online sources (e.g Google Maps and Stamen Maps). It includes tools common to those tasks, including functions for geolocation and routing.

URL <https://github.com/dkahle/ggmap>

BugReports <https://github.com/dkahle/ggmap/issues>

Depends R (>= 3.1.0), ggplot2 (>= 2.2.0)

Imports png, plyr, jpeg, digest, scales, dplyr, bitops, grid, glue, httr, stringr, purrr, magrittr, tibble, tidyr, rlang, cli

Suggests MASS, hexbin, testthat

License GPL-2

LazyData true

RoxygenNote 7.2.3

Roxygen list(markdown = TRUE)

Encoding UTF-8

Repository <https://dkahle.r-universe.dev>

RemoteUrl <https://github.com/dkahle/ggmap>

RemoteRef HEAD

RemoteSha 8b12bebcc95b6ed2fe211580a88f0b47922baf4b

Contents

| | |
|----------------------------|----|
| bb2bbox | 2 |
| calc_zoom | 4 |
| crime | 5 |
| geocode | 5 |
| geom_leg | 8 |
| get_cloudmademap | 10 |

| | |
|-------------------------------|-----------|
| get_googlemap | 12 |
| get_map | 15 |
| get_navermap | 17 |
| get_openstreetmap | 19 |
| get_stadiamap | 20 |
| get_stamenmap | 23 |
| ggimage | 25 |
| gglocator | 26 |
| ggmap | 27 |
| ggmap-defunct | 36 |
| ggmapplot | 36 |
| ggmap_options | 37 |
| hadley | 38 |
| inset | 38 |
| inset_raster | 39 |
| legs2route | 40 |
| LonLat2XY | 41 |
| make_bbox | 42 |
| mapdist | 43 |
| OSM_scale_lookup | 46 |
| print.ggmap | 47 |
| qmap | 48 |
| qplot | 49 |
| register_google | 54 |
| register_stadiamaps | 57 |
| revgeocode | 59 |
| route | 60 |
| theme_inset | 62 |
| theme_nothing | 63 |
| trek | 64 |
| wind | 67 |
| XY2LonLat | 67 |
| zips | 68 |
| Index | 70 |

bb2bbox

Convert a bb specification to a bbox specification

Description

In ggmap, all maps (class ggmap) have the bb attribute, a data frame bounding box specification in terms of the bottom left and top right points of the spatial extent. This function converts this specification to a named double vector (with names left, bottom, right, top) specification that is used in some querying functions (e.g. get_stadiamap).

Usage

```
bb2bbox(bb)
```

Arguments

bb a bounding box in bb format (see examples)

Value

a bounding box in bbox format (see examples)

Author(s)

David Kahle <david@kahle.io>

Examples

```
## Not run: # cut down on R CMD check time

# grab a center/zoom map and compute its bounding box
gc <- geocode("white house, washington dc")
map <- get_map(gc)
(bb <- attr(map, "bb"))
(bbox <- bb2bbox(bb))

# use the bounding box to get a Stadia map
stadMap <- get_stadiamap(bbox)

ggmap(map) +
  geom_point(
    aes(x = lon, y = lat),
    data = gc, colour = "red", size = 3
  )

ggmap(stadMap) +
  geom_point(
    aes(x = lon, y = lat),
    data = gc, colour = "red", size = 3
  )

## End(Not run)
```

`calc_zoom`*Calculate a zoom given a bounding box*

Description

`calc_zoom` can calculate a zoom based on either (1) a data frame with longitude and latitude variables, (2) a longitude range and latitude range, or (3) a bounding box (bbox specification). The specification for (1) is identical to that of most R functions, for (2) simply put in a longitude range into `lon` and a latitude range into `lat`, and for (3) put the bounding box in for the `lon` argument.

Usage

```
calc_zoom(lon, lat, data, adjust = 0, f = 0.05)
```

Arguments

| | |
|---------------------|---|
| <code>lon</code> | longitude, see details |
| <code>lat</code> | latitude, see details |
| <code>data</code> | (optional) a data frame containing <code>lon</code> and <code>lat</code> as variables |
| <code>adjust</code> | number to add to the calculated zoom |
| <code>f</code> | argument to pass to <code>make_bbox</code> |

See Also

[make_bbox\(\)](#), [bb2bbox\(\)](#)

Examples

```
# From data
calc_zoom(lon, lat, wind)

# From range
lon_range <- extendrange( wind$lon )
lat_range <- extendrange( wind$lat )
calc_zoom(lon_range, lat_range)

# From bounding box
box <- make_bbox(lon, lat, data = crime)
calc_zoom(box)
```

crime

Crime data

Description

Lightly cleaned Houston crime from January 2010 to August 2010 geocoded with Google Maps

Author(s)

Houston Police Department, City of Houston

References

<https://www.houstontx.gov/police/cs/index-2.htm>

geocode

Geocode

Description

Geocodes (finds latitude and longitude of) a location using the Google Geocoding API. Note: To use Google's Geocoding API, you must first enable the API in the Google Cloud Platform Console. See [register_google\(\)](#).

Usage

```
geocode(  
  location,  
  output = c("latlon", "latlon", "more", "all"),  
  source = c("google", "dsk"),  
  force = ifelse(source == "dsk", FALSE, TRUE),  
  urlonly = FALSE,  
  override_limit = FALSE,  
  nameType = c("long", "short"),  
  ext = "com",  
  inject = "",  
  ...  
)
```

```
mutate_geocode(data, location, ...)
```

```
geocodeQueryCheck()
```

```
geocode_cache()
```

```
write_geocode_cache(path, ...)
```

```
load_geocode_cache(path, overwrite = FALSE)
```

```
clear_geocode_cache(path)
```

Arguments

| | |
|----------------|--|
| location | a character vector of street addresses or place names (e.g. "1600 pennsylvania avenue, washington dc") |
| output | amount of output, "latlon", "latlona", "more", or "all" |
| source | "google" for Google (note: "dsk" is defunct) |
| force | force online query even if cached. |
| urlonly | return only the url? |
| override_limit | override the current query rate |
| nameType | in some cases, Google returns both a long name and a short name. this parameter allows the user to specify which to grab. |
| ext | top level domain (e.g. "com", "co.nz"); helpful for non-US users |
| inject | character string to add to the url or named character vector of key-value pairs to be injected (e.g. c("a" = "b") get converted to "a=b" and appended to the query) |
| ... | In <code>mutate_geocode()</code> , arguments to pass to <code>geocode()</code> . In <code>write_geocode_cache()</code> , arguments to pass to <code>saveRDS()</code> . |
| data | a data frame or equivalent |
| path | path to file |
| overwrite | in <code>load_geocode_cache()</code> , should the current cache be wholly replaced with the one on file? |

Details

Note: `geocode()` uses Google's Geocoding API to geocode addresses. Please take care not to disclose sensitive information. <https://www.ncbi.nlm.nih.gov/pmc/articles/PMC8972108/> suggest various alternative options for such data.

Value

If output is "latlon", "latlona", or "more", a tibble (classed data frame). If "all", a list.

Author(s)

David Kahle <david@kahle.io>

See Also

<https://developers.google.com/maps/documentation/geocoding/>, <https://developers.google.com/maps/documentation/javascript/geocoding/>, <https://developers.google.com/maps/documentation/geocoding/usage-and-billing/>, <https://www.ncbi.nlm.nih.gov/pmc/articles/PMC8972108/>

Examples

```
## Not run:  requires Google API key, see ?register_google

## basic usage
#####

# geocoding is most commonly used for addresses
geocode("1600 Amphitheatre Parkway, Mountain View, CA")
geocode("1600 Amphitheatre Parkway, Mountain View, CA", urlonly = TRUE)

# google can also geocode colloquial names of places
geocode("the white house")

# geocode can also accept character vectors of places
geocode(c("the white house", "washington dc"))

## types of output
#####

geocode("waco texas")
geocode("waco texas", output = "latlona")
geocode("waco texas", output = "more")
str(geocode("waco texas", output = "all"))

geocode(c("waco, texas", "houston, texas"))
geocode(c("waco, texas", "houston, texas"), output = "latlona")
geocode(c("waco, texas", "houston, texas"), output = "all") %>% str(4)

## mutate_geocode
#####

# mutate_geocode is used to add location columns to an existing dataset
# that has location information

df <- data.frame(
  address = c("1600 Pennsylvania Avenue, Washington DC", "", "houston texas"),
  stringsAsFactors = FALSE
)

mutate_geocode(df, address)
df %>% mutate_geocode(address)

## known issues
#####

# in some cases geocode finds several locations
```

```
## End(Not run)
```

```
geom_leg
```

```
Single line segments with rounded ends
```

Description

This is ggplot2's segment with rounded ends. It's mainly included in ggmap for historical reasons.

Usage

```
geom_leg(
  mapping = NULL,
  data = NULL,
  stat = "identity",
  position = "identity",
  arrow = NULL,
  lineend = "round",
  na.rm = FALSE,
  show.legend = NA,
  inherit.aes = TRUE,
  ...
)
```

Arguments

| | |
|---------|---|
| mapping | Set of aesthetic mappings created by aes() . If specified and <code>inherit.aes = TRUE</code> (the default), it is combined with the default mapping at the top level of the plot. You must supply mapping if there is no plot mapping. |
| data | The data to be displayed in this layer. There are three options: If <code>NULL</code> , the default, the data is inherited from the plot data as specified in the call to ggplot() . A <code>data.frame</code> , or other object, will override the plot data. All objects will be fortified to produce a data frame. See fortify() for which variables will be created. A function will be called with a single argument, the plot data. The return value must be a <code>data.frame</code> , and will be used as the layer data. A function can be created from a formula (e.g. <code>~ head(.x, 10)</code>). |
| stat | The statistical transformation to use on the data for this layer, either as a ggproto Geom subclass or as a string naming the stat stripped of the <code>stat_</code> prefix (e.g. "count" rather than "stat_count") |

| | |
|-------------|---|
| position | Position adjustment, either as a string naming the adjustment (e.g. "jitter" to use position_jitter), or the result of a call to a position adjustment function. Use the latter if you need to change the settings of the adjustment. |
| arrow | specification for arrow heads, as created by <code>grid::arrow()</code> . |
| lineend | Line end style (round, butt, square). |
| na.rm | If FALSE, the default, missing values are removed with a warning. If TRUE, missing values are silently removed. |
| show.legend | logical. Should this layer be included in the legends? NA, the default, includes if any aesthetics are mapped. FALSE never includes, and TRUE always includes. It can also be a named logical vector to finely select the aesthetics to display. |
| inherit.aes | If FALSE, overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. <code>borders()</code> . |
| ... | Other arguments passed on to <code>layer()</code> . These are often aesthetics, used to set an aesthetic to a fixed value, like <code>colour = "red"</code> or <code>size = 3</code> . They may also be parameters to the paired geom/stat. |

Details

only intended for use in ggmap package. only designed for mercator projection.

See Also

[geom_segment\(\)](#), [route\(\)](#), inspired by <http://spatialanalysis.co.uk/2012/02/great-maps-ggplot2/>, no longer active

Examples

```
## Not run: # removed for R CMD check speed

map <- get_map(
  location = c(-77.0425, 38.8925), # painfully picked by hand
  source = "google", zoom = 14, maptype = "satellite"
)
ggmap(map)

(legs_df <- route(
  "the white house, dc",
  "lincoln memorial washington dc",
  alternatives = TRUE
))

ggplot(data = legs_df) +
  geom_leg(aes(
    x = start_lon, xend = end_lon,
    y = start_lat, yend = end_lat
  )) +
  coord_map()
```

```
ggplot(data = legs_df) +
  geom_leg(aes(
    x = start_lon, xend = end_lon,
    y = start_lat, yend = end_lat,
    color = route
  )) +
  coord_map()

ggmap(map) +
  geom_leg(
    aes(
      x = start_lon, xend = end_lon,
      y = start_lat, yend = end_lat
    ),
    data = legs_df, color = "red"
  )

# adding a color aesthetic errors because of a base-layer problem
# ggmap(map) +
#   geom_leg(
#     aes(
#       x = start_lon, xend = end_lon,
#       y = start_lat, yend = end_lat,
#       color = route
#     )
#   )

# this is probably the easiest hack to fix it
ggplot(data = legs_df) +
  inset_ggmap(map) +
  geom_leg(
    aes(
      x = start_lon, xend = end_lon,
      y = start_lat, yend = end_lat,
      color = route
    ),
    data = legs_df
  ) +
  coord_map()

## End(Not run)
```

Description

`get_cloudmademap()` accesses a tile server for Stamen Maps and downloads/stitches map tiles/formats a map image. This function requires an api key which can be obtained for free from <http://cloudmade.com/user/show>, now defunct. Thousands of maptypes ("styles"), including create-your-own options, are available from <http://maps.cloudmade.com/editor> (defunct).

Usage

```
get_cloudmademap(
  bbox = c(left = -95.80204, bottom = 29.38048, right = -94.92313, top = 30.14344),
  zoom = 10,
  api_key,
  matype = 1,
  highres = TRUE,
  crop = TRUE,
  messaging = FALSE,
  urlonly = FALSE,
  filename = NULL,
  color = c("color", "bw"),
  ...
)
```

Arguments

| | |
|------------------------|---|
| <code>bbox</code> | a bounding box in the format <code>c(lowerleftlon, lowerleftlat, upperrightlon, upperrightlat)</code> . |
| <code>zoom</code> | a zoom level |
| <code>api_key</code> | character string containing cloud made api key, see details |
| <code>matype</code> | an integer of what cloud made calls style, see details |
| <code>highres</code> | double resolution |
| <code>crop</code> | crop raw map tiles to specified bounding box |
| <code>messaging</code> | turn messaging on/off |
| <code>urlonly</code> | return url only |
| <code>filename</code> | destination file for download (file extension added according to format). Default NULL means a random <code>tempfile()</code> . |
| <code>color</code> | color or black-and-white |
| <code>...</code> | ... |

Value

a ggmap object (a classed raster object with a bounding box attribute)

Author(s)

David Kahle <david@kahle.io>

See Also

<http://maps.cloudmade.com/> (defunct), [ggmap\(\)](#)

get_googlemap

Get a Google Map.

Description

[get_googlemap\(\)](#) queries the Google Maps Static API version 2 to download a static map. Note that in most cases by using this function you are agreeing to the Google Maps API Terms of Service at <https://cloud.google.com/maps-platform/terms/>. Note that as of mid-2018, registering with Google Cloud to obtain an API key is required to use any of Google's services, including [get_googlemap\(\)](#). Usage and billing may apply, see the links under See Also further down in this documentation for more details.

Usage

```
get_googlemap(
  center = c(lon = -95.3632715, lat = 29.7632836),
  zoom = 10,
  size = c(640, 640),
  scale = 2,
  format = c("png8", "gif", "jpg", "jpg-baseline", "png32"),
  maptype = GOOGLE_VALID_MAP_TYPES,
  language = "en-EN",
  messaging = FALSE,
  urlonly = FALSE,
  filename = NULL,
  color = c("color", "bw"),
  force = FALSE,
  where = tempdir(),
  archiving = FALSE,
  ext = "com",
  inject = "",
  region,
  markers,
  path,
  visible,
  style,
  ...
)
```

Arguments

center the center of the map; either a longitude/latitude numeric vector or a string containing a location, in which case [geocode\(\)](#) is called with source = "google". (default: `c(lon = -95.3632715, lat = 29.7632836)`, a reference to Houston, Texas)

| | |
|-----------|--|
| zoom | map zoom; an integer from 3 (continent) to 21 (building), default value 10 (city) |
| size | rectangular dimensions of map in pixels - horizontal x vertical - with a max of c(640, 640). this parameter is affected in a multiplicative way by scale. |
| scale | multiplicative factor for the number of pixels returned possible values are 1, 2, or 4 (e.g. size = c(640,640) and scale = 2 returns an image with 1280x1280 pixels). 4 is reserved for google business users only. scale also affects the size of labels as well. |
| format | character string providing image format - png, jpeg, and gif formats available in various flavors |
| maptype | character string providing google map theme. options available are "terrain", "satellite", "roadmap", and "hybrid" |
| language | character string providing language of map labels (for themes with them) in the format "en-EN". not all languages are supported; for those which aren't the default language is used |
| messaging | turn messaging on/off |
| urlonly | return url only |
| filename | destination file for download (file extension added according to format). Default NULL means a random <code>tempfile()</code> . |
| color | color or black-and-white |
| force | if the map is on file, should a new map be looked up? |
| where | where should the file drawer be located (without terminating "/") |
| archiving | use archived maps. note: by changing to TRUE you agree to the one of the approved uses listed in the Google Maps API Terms of Service : https://cloud.google.com/maps-platform/terms/ . |
| ext | domain extension (e.g. "com", "co.nz") |
| inject | character string to add to the url |
| region | borders to display as a region code specified as a two-character ccTLD ("top-level domain") value, see https://en.wikipedia.org/wiki/List_of_Internet_top-level_domains#Country_code_top-level_domains |
| markers | data.frame with first column longitude, second column latitude, for which google markers should be embedded in the map image, or character string to be passed directly to api |
| path | data.frame (or list of data.frames) with first column longitude, second column latitude, for which a single path should be embedded in the map image, or character string to be passed directly to api |
| visible | a location as a longitude/latitude numeric vector (or data frame with first column longitude, second latitude) or vector of character string addresses which should be visible in map extent |
| style | character string to be supplied directly to the api for the style argument or a named vector (see examples). this is a powerful complex specification, see https://developers.google.com/maps/documentation/maps-static/ |
| ... | ... |

Value

a ggmap object (a classed raster object with a bounding box attribute)

Author(s)

David Kahle <david@kahle.io>

See Also

<https://developers.google.com/maps/documentation/maps-static/overview/>, <https://developers.google.com/maps/documentation/maps-static/start/>, <https://developers.google.com/maps/documentation/maps-static/get-api-key/>, <https://developers.google.com/maps/documentation/maps-static/usage-and-billing/>, [ggmap\(\)](#), [register_google\(\)](#)

Examples

```
## Not run:  requires Google API key, see ?register_google

## basic usage
#####

(map <- get_googlemap(c(-97.14667, 31.5493)))
ggmap(map)

# plotting based on a colloquial name
# this requires a geocode() call, and needs that API
get_googlemap("waco, texas") %>% ggmap()

# different maptypes are available
get_googlemap("waco, texas", maptype = "satellite") %>% ggmap()
get_googlemap("waco, texas", maptype = "hybrid") %>% ggmap()

# you can get the url as follows
# see ?register_google if you want the key printed
get_googlemap(urlonly = TRUE)

## other usage
#####

# markers and paths are easy to access
d <- function(x=-95.36, y=29.76, n,r,a){
  round(data.frame(
    lon = jitter(rep(x,n), amount = a),
    lat = jitter(rep(y,n), amount = a)
  ), digits = r)
}
(df <- d(n = 50, r = 3, a = .3))
map <- get_googlemap(markers = df, path = df, scale = 2)
ggmap(map)
ggmap(map, extent = "device") +
  geom_point(aes(x = lon, y = lat), data = df, size = 3, colour = "black") +
```

```
geom_path(aes(x = lon, y = lat), data = df)

gc <- geocode("waco, texas", source = "google")
center <- as.numeric(gc)
ggmap(get_googlemap(center = center, color = "bw", scale = 2), extent = "device")

# the scale argument can be seen in the following
# (make your graphics device as large as possible)
ggmap(get_googlemap(center, scale = 1), extent = "panel") # pixelated
ggmap(get_googlemap(center, scale = 2), extent = "panel") # fine

# archiving; note that you must meet google's terms for this condition
map <- get_googlemap(archiving = TRUE)
map <- get_googlemap()
map <- get_googlemap()
ggmap(map)

# style
map <- get_googlemap(
  maptype = "roadmap",
  style = c(feature = "all", element = "labels", visibility = "off"),
  color = "bw"
)
ggmap(map)

## End(Not run)
```

get_map

Grab a map.

Description

`get_map()` is a smart wrapper that queries the Google Maps, OpenStreetMap, and Stadia Maps servers for a map.

Usage

```
get_map(
  location = c(lon = -95.3632715, lat = 29.7632836),
  zoom = "auto",
  scale = "auto",
  maptype = c(GOOGLE_VALID_MAP_TYPES, STADIA_VALID_MAP_TYPES),
  source = c("google", "osm", "stadia"),
  force = ifelse(source == "google", TRUE, FALSE),
```

```

    messaging = FALSE,
    urlonly = FALSE,
    filename = NULL,
    crop = TRUE,
    color = c("color", "bw"),
    language = "en-EN",
    ...
)

```

Arguments

| | |
|-----------|---|
| location | an address, longitude/latitude pair (in that order), or left/bottom/right/top bounding box |
| zoom | map zoom, an integer from 3 (continent) to 21 (building), default value 10 (city). openstreetmaps limits a zoom of 18, and the limit on Stadia Maps depends on the maptype. "auto" automatically determines the zoom for bounding box specifications, and is defaulted to 10 with center/zoom specifications. maps of the whole world currently not supported. |
| scale | scale argument of get_googlemap() or get_openstreetmap() |
| maptype | character string providing map theme. options available are "terrain", "terrain-background", "satellite", "roadmap", and "hybrid" (Google Maps), "stamen_terrain", "stamen_toner", "stamen_toner_lite", "stamen_watercolor", "stamen_terrain_background", "stamen_toner_background", "stamen_terrain_lines", "stamen_terrain_labels", "stamen_toner_lines", "stamen_toner_labels" (Stadia Maps) |
| source | Google Maps ("google"), OpenStreetMap ("osm"), Stadia Maps ("stadia") |
| force | force new map (don't use archived version) |
| messaging | turn messaging on/off |
| urlonly | return url only |
| filename | destination file for download (file extension added according to format). Default NULL means a random tempfile() . |
| crop | (Stadia and cloudmade maps) crop tiles to bounding box |
| color | color ("color") or black-and-white ("bw") |
| language | language for google maps |
| ... | ... |

Value

a ggmap object (a classed raster object with a bounding box attribute)

Author(s)

David Kahle <david@kahle.io>

See Also

[ggmap\(\)](#)

Examples

```
## Not run: some requires Google API key, see ?register_google

## basic usage
#####

# lon-lat vectors automatically use google:
(map <- get_map(c(-97.14667, 31.5493)))
str(map)
ggmap(map)

# bounding boxes default to Stadia Maps
(map <- get_map(c(left = -97.1268, bottom = 31.536245, right = -97.099334, top = 31.559652)))
ggmap(map)

# characters default to google
(map <- get_map("orlando, florida"))
ggmap(map)

## basic usage
#####

(map <- get_map(maptypes = "roadmap"))
(map <- get_map(source = "osm"))
(map <- get_map(source = "stadia", maptype = "stamen_watercolor"))

map <- get_map(location = "texas", zoom = 6, source = "stadia")
ggmap(map, fullpage = TRUE)

## End(Not run)
```

get_navermap

Get a Naver Map

Description

This is (at least) temporarily unavailable as the Naver API changed.

Usage

```
get_navermap(
  center = c(lon = 126.9849208, lat = 37.5664519),
  zoom = 4,
  size = c(640, 640),
  format = c("png", "jpeg", "jpg"),
  crs = c("EPSG:4326", "NHN:2048", "NHN:128", "EPSG:4258", "EPSG:4162", "EPSG:2096",
    "EPSG:2097", "EPSG:2098", "EPSG:900913"),
```

```

baselayer = c("default", "satellite"),
color = c("color", "bw"),
overlayers = c("anno_satellite", "bicycle", "roadview", "traffic"),
markers,
key,
uri,
filename = NULL,
messaging = FALSE,
urlonly = FALSE,
force = FALSE,
where = tempdir(),
archiving = TRUE,
...
)

```

Arguments

| | |
|------------|---|
| center | the center of the map. this can be longitude/latitude numeric vector. |
| zoom | map zoom, an integer from 1 to 14 (building), default value 10 |
| size | rectangular dimensions of map in pixels - horizontal x vertical - with a max of c(640, 640). |
| format | character string providing image format - png, jpeg(jpg) formats available in various flavors |
| crs | Coordinate system, this currently supports EPSG:4326 |
| baselayer | base layer, this can be either "default", "satellite". |
| color | color or black-and-white |
| overlayers | overlay layers, this can be "anno_satellite", "bicycle", "roadview", "traffic". |
| markers | data.frame with first column longitude, second column latitude, for which naver markers should be embedded in the map image, or character string to be passed directly to api |
| key | key code from naver api center |
| uri | registered host url |
| filename | destination file for download (file extension added according to format). Default NULL means a random <code>tempfile()</code> . |
| messaging | turn messaging on/off |
| urlonly | return url only |
| force | if the map is on file, should a new map be looked up? |
| where | where should the file drawer be located (without terminating "/") |
| archiving | use archived maps. note: by changing to TRUE you agree to abide by any of the rules governing caching naver maps |
| ... | ... |

Details

[get_navermap\(\)](#) accesses the Naver Static Maps API version 1.1 to download a static map. Note that in most cases by using this function you are agreeing to the Naver Maps API Terms of Service.

Author(s)

Heewon Jeon <madjakarta@gmail.com>

See Also

[ggmap\(\)](#)

get_openstreetmap *Get an OpenStreetMap*

Description

[get_openstreetmap\(\)](#) accesses a tile server for OpenStreetMap and downloads/formats a map image. This is simply a wrapper for the web-based version at <https://www.openstreetmap.org/>. If you don't know how to get the map you want, go there, navigate to the map extent that you want, click the export tab at the top of the page, and copy the information into this function.

Usage

```
get_openstreetmap(  
  bbox = c(left = -95.80204, bottom = 29.38048, right = -94.92313, top = 30.14344),  
  scale = 606250,  
  format = c("png", "jpeg", "svg", "pdf", "ps"),  
  messaging = FALSE,  
  urlonly = FALSE,  
  filename = NULL,  
  color = c("color", "bw"),  
  ...  
)
```

Arguments

| | |
|-------|---|
| bbox | a bounding box in the format c(lowerleftlon, lowerleftlat, upperrightlon, upperrightlat) |
| scale | scale parameter, see https://wiki.openstreetmap.org/wiki/MinScaleDenominator . smaller scales provide a finer degree of detail, where larger scales produce more coarse detail. The scale argument is a tricky number to correctly specify. In most cases, if you get an error when downloading an openstreetmap the error is attributable to an improper scale specification. OSM_scale_lookup() can help; but the best way to get in the correct range is to go to https://www.openstreetmap.org/ , navigate to the map of interest, click export at the top of the page, click 'map image' and then copy down the scale listed. |

| | |
|-----------|---|
| format | character string providing image format - png, jpeg, svg, pdf, and ps formats |
| messaging | turn messaging on/off |
| urlonly | return url only |
| filename | destination file for download (file extension added according to format). Default NULL means a random <code>tempfile()</code> . |
| color | color or black-and-white |
| ... | ... |

Details

In some cases the OSM server is unavailable, in these cases you will receive an error message from `utils::download.file()` with the message HTTP status '503 Service Unavailable'. You can confirm this by setting `urlonly = TRUE`, and then entering the URL in a web browser. the solution is either (1) change sources or (2) wait for the OSM servers to come back up.

See <https://www.openstreetmap.org/copyright/> for license and copyright information.

Value

a ggmap object (a classed raster object with a bounding box attribute)

Author(s)

David Kahle <david@kahle.io>

See Also

<https://www.openstreetmap.org/>, `ggmap()`

get_stadiamap

Get a Map from Stadia Maps

Description

`get_stadiamap()` accesses a tile server for Stadia Maps and downloads/stitches map tiles/formats a map image.

Usage

```
get_stadiamap(
  bbox = c(left = -95.80204, bottom = 29.38048, right = -94.92313, top = 30.14344),
  zoom = 10,
  maptype = STADIA_VALID_MAP_TYPES,
  crop = TRUE,
  messaging = FALSE,
  urlonly = FALSE,
  color = c("color", "bw"),
```

```

    force = FALSE,
    where = tempdir(),
    ...
)

```

Arguments

| | |
|-----------|---|
| bbox | a bounding box in the format c(lowerleftlon, lowerleftlat, upperrightlon, upperrightlat). |
| zoom | a zoom level |
| maptype | stamen_terrain, stamen_toner, stamen_toner_lite, stamen_watercolor, stamen_terrain_background, stamen_toner_background, stamen_terrain_lines, stamen_terrain_labels, stamen_toner_lines, stamen_toner_labels. |
| crop | crop raw map tiles to specified bounding box. if FALSE, the resulting map will more than cover the bounding box specified. |
| messaging | turn messaging on/off |
| urlonly | return url only |
| color | color or black-and-white (use force = TRUE if you've already downloaded the images) |
| force | if the map is on file, should a new map be looked up? |
| where | where should the file drawer be located (without terminating "/") |
| ... | ... |

Value

a ggmap object (a classed raster object with a bounding box attribute)

See Also

<https://docs.stadiamaps.com/themes/>, `ggmap()`

Examples

```

## Not run:  requires a Stadia Maps API key. see ?register_stadiamaps

## basic usage
#####

bbox <- c(left = -97.1268, bottom = 31.536245, right = -97.099334, top = 31.559652)

ggmap(get_stadiamap(bbox, zoom = 13))
ggmap(get_stadiamap(bbox, zoom = 14))
ggmap(get_stadiamap(bbox, zoom = 15))
ggmap(get_stadiamap(bbox, zoom = 17, messaging = TRUE))

place <- "mount everest"
(google <- get_googlemap(place, zoom = 9))

```

```

ggmap(google)
bbox_everest <- c(left = 86.05, bottom = 27.21, right = 87.81, top = 28.76)
ggmap(get_stadiamap(bbox_everest, zoom = 9))

## map types
#####

place <- "rio de janeiro"
google <- get_googlemap(place, zoom = 10)
ggmap(google)

bbox <- bb2bbox(attr(google, "bb"))

get_stadiamap(bbox, maptype = "stamen_terrain")           %>% ggmap()
get_stadiamap(bbox, maptype = "stamen_terrain_background") %>% ggmap()
get_stadiamap(bbox, maptype = "stamen_terrain_labels")   %>% ggmap()
get_stadiamap(bbox, maptype = "stamen_terrain_lines")   %>% ggmap()
get_stadiamap(bbox, maptype = "stamen_toner")           %>% ggmap()
get_stadiamap(bbox, maptype = "stamen_toner_background") %>% ggmap()
get_stadiamap(bbox, maptype = "stamen_toner_labels")    %>% ggmap()
get_stadiamap(bbox, maptype = "stamen_toner_lines")    %>% ggmap()
get_stadiamap(bbox, maptype = "stamen_toner_lite")     %>% ggmap()
get_stadiamap(bbox, maptype = "stamen_watercolor")     %>% ggmap()

## zoom levels
#####

get_stadiamap(bbox, maptype = "stamen_watercolor", zoom = 11) %>% ggmap(extent = "device")
get_stadiamap(bbox, maptype = "stamen_watercolor", zoom = 12) %>% ggmap(extent = "device")
get_stadiamap(bbox, maptype = "stamen_watercolor", zoom = 13) %>% ggmap(extent = "device")
# get_stadiamap(bbox, maptype = "stamen_watercolor", zoom = 14) %>% ggmap(extent = "device")
# get_stadiamap(bbox, maptype = "stamen_watercolor", zoom = 15) %>% ggmap(extent = "device")
# get_stadiamap(bbox, maptype = "stamen_watercolor", zoom = 16) %>% ggmap(extent = "device")
# get_stadiamap(bbox, maptype = "stamen_watercolor", zoom = 17) %>% ggmap(extent = "device")
# get_stadiamap(bbox, maptype = "stamen_watercolor", zoom = 18) %>% ggmap(extent = "device")

## more examples
#####

gc <- geocode("rio de janeiro")

get_stadiamap(bbox, zoom = 10) %>% ggmap() +
  geom_point(aes(x = lon, y = lat), data = gc, colour = "red", size = 2)

get_stadiamap(bbox, zoom = 10, crop = FALSE) %>% ggmap() +
  geom_point(aes(x = lon, y = lat), data = gc, colour = "red", size = 2)

get_stadiamap(bbox, zoom = 10, maptype = "stamen_watercolor") %>% ggmap() +
  geom_point(aes(x = lon, y = lat), data = gc, colour = "red", size = 2)

```

```

get_stadiamap(bbox, zoom = 10, maptype = "stamen_toner") %>% ggmap() +
  geom_point(aes(x = lon, y = lat), data = gc, colour = "red", size = 2)

# continental united states labels
c("left" = -125, "bottom" = 25.75, "right" = -67, "top" = 49) %>%
  get_stadiamap(zoom = 5, maptype = "stamen_toner_labels") %>%
  ggmap()

# accuracy check - white house
gc <- geocode("the white house")

qmap("the white house", zoom = 16) +
  geom_point(aes(x = lon, y = lat), data = gc, colour = "red", size = 3)

qmap("the white house", zoom = 16, source = "stadia", maptype = "stamen_terrain") +
  geom_point(aes(x = lon, y = lat), data = gc, colour = "red", size = 3)

## known issues
#####

# Stamen's original tilesets were raster renders built up over time, but have not been
# actively rendered for several years. As a consequence, some tiles simply do not exist,
# particularly at high zoom levels.
#
# The newer styles have been redesigned and are now generated live by Stadia Maps, so
# these are complete, but at the time of this writing, the Watercolor style is still incomplete.

## End(Not run)

```

get_stamenmap

Get a Stamen Map

Description

`get_stamenmap()` accesses a tile server for Stamen Maps and downloads/stitches map tiles/formats a map image. Note that Stamen maps don't cover the entire world.

Usage

```

get_stamenmap(
  bbox = c(left = -95.80204, bottom = 29.38048, right = -94.92313, top = 30.14344),
  zoom = 10,
  maptype = c("terrain", "terrain-background", "terrain-labels", "terrain-lines",
    "toner", "toner-2010", "toner-2011", "toner-background", "toner-hybrid",

```

```

    "toner-labels", "toner-lines", "toner-lite", "watercolor"),
  crop = TRUE,
  messaging = FALSE,
  urlonly = FALSE,
  color = c("color", "bw"),
  force = FALSE,
  where = tempdir(),
  https = FALSE,
  ...
)

get_stamen_tile_download_fail_log()

retry_stamen_map_download()

```

Arguments

| | |
|-----------|--|
| bbox | a bounding box in the format c(lowerleftlon, lowerleftlat, upperrightlon, upperrightlat). |
| zoom | a zoom level |
| maptype | terrain, terrain-background, terrain-labels, terrain-lines, toner, toner-2010, toner-2011, toner-background, toner-hybrid, toner-labels, toner-lines, toner-lite, or watercolor. |
| crop | crop raw map tiles to specified bounding box. if FALSE, the resulting map will more than cover the bounding box specified. |
| messaging | turn messaging on/off |
| urlonly | return url only |
| color | color or black-and-white (use force = TRUE if you've already downloaded the images) |
| force | if the map is on file, should a new map be looked up? |
| where | where should the file drawer be located (without terminating "/") |
| https | if TRUE, queries an https endpoint so that web traffic between you and the tile server is encrypted using SSL. |
| ... | ... |

Value

a ggmap object (a classed raster object with a bounding box attribute)

See Also

[ggmap\(\)](#)

`ggimage`*Plot an image using ggplot2*

Description

`ggimage` is the near `ggplot2` equivalent of `image`.

Usage

```
ggimage(mat, fullpage = TRUE, coord_equal = TRUE, scale_axes = FALSE)
```

Arguments

| | |
|--------------------------|--|
| <code>mat</code> | a matrix, <code>imagematrix</code> , array, or raster (something that can be coerced by <code>as.raster</code>) |
| <code>fullpage</code> | should the image take up the entire viewport? |
| <code>coord_equal</code> | should the axes units be equal? |
| <code>scale_axes</code> | should the axes be (0,ncol(mat)-1)x(0,nrow(mat)-1) (F) or (0,1)x(0,1) (T) |

Value

a `ggplot` object

Author(s)

David Kahle <david@kahle.io>

Examples

```
img <- matrix(1:16, 4, 4)
image(img)
ggimage(t(img[,4:1]), fullpage = FALSE, scale_axes = TRUE)
ggimage(t(img[,4:1]), fullpage = FALSE)

## Not run:
# not run due to slow performance

data(hadley)
ggimage(hadley)
ggimage(hadley, coord_equal = FALSE)

x <- seq(1, 438, 15); n <- length(x)
df <- data.frame(x = x, y = -(120*(scale((x - 219)^3 - 25000*x) + rnorm(n)/2 - 3)))
qplot(x, y, data = df, geom = c('smooth', 'point'))
ggimage(hadley, fullpage = FALSE) +
  geom_smooth(
    aes(x = x, y = y),
    data = df, color = 'green', size = 1
```

```

) +
geom_point(
  aes(x = x, y = y),
  data = df, color = 'green', size = 3
)

## End(Not run)

```

gglocator

Locator for ggplot objects

Description

Locator for ggplot objects (Note : only accurate when extent = "normal" when using ggmap.)

Usage

```
gglocator(n = 1, message = FALSE, mercator = TRUE, ...)
```

Arguments

| | |
|----------|--|
| n | number of points to locate. |
| message | unused |
| mercator | logical flag; should the plot be treated as using the projection common to most web map services? Set to FALSE if the axes on the plot use a linear scale. |
| ... | additional arguments (including deprecated, e.g. xexpand) |

Value

a data frame with columns according to the x and y aesthetics

Author(s)

Tyler Rinker, Baptiste Auguie, DWin, David Kahle, \@Nikolai-Hlubek and \@mvkorpel.

Examples

```

if (interactive()) {

# only run for interactive sessions
df <- expand.grid(x = 0:-5, y = 0:-5)

ggplot(df, aes(x, y)) + geom_point() +
  annotate(geom = "point", x = -2, y = -2, colour = "red")

(pt <- gglocator(mercator = FALSE)) # click red point

```

```

last_plot() +
  annotate("point", pt$x, pt$y, color = "blue", size = 3, alpha = .5)

hdf <- get_map("houston, texas")
ggmap(hdf, extent = "normal")
(pt <- gglocator(mercator = TRUE))
last_plot() +
  annotate("point", pt$lon, pt$lat, color = "blue", size = 3, alpha = .5)

}

```

ggmap

*Plot a ggmap object***Description**

ggmap plots the raster object produced by [get_map\(\)](#).

Usage

```

ggmap(
  ggmap,
  extent = "panel",
  base_layer,
  maprange = FALSE,
  legend = "right",
  padding = 0.02,
  darken = c(0, "black"),
  b,
  fullpage,
  expand,
  ...
)

```

Arguments

| | |
|------------|--|
| ggmap | an object of class ggmap (from function get_map) |
| extent | how much of the plot should the map take up? "normal", "device", or "panel" (default) |
| base_layer | a ggplot(aes(...), ...) call; see examples |
| maprange | logical for use with base_layer; should the map define the x and y limits? |
| legend | "left", "right" (default), "bottom", "top", "bottomleft", "bottomright", "topleft", "topright", "none" (used with extent = "device") |
| padding | distance from legend to corner of the plot (used with legend, formerly b) |

| | |
|----------|--|
| darken | vector of the form <code>c(number, color)</code> , where <code>number</code> is in (0,1) and <code>color</code> is a character string indicating the color of the darken. 0 indicates no darkening, 1 indicates a black-out. |
| b | Deprecated, renamed to <code>padding</code> . Overrides any <code>padding</code> argument. |
| fullpage | Deprecated, equivalent to <code>extent = "device"</code> when TRUE. Overrides any <code>extent</code> argument. |
| expand | Deprecated, equivalent to <code>extent = "panel"</code> when TRUE and <code>fullpage</code> is FALSE. When <code>fullpage</code> is FALSE and <code>expand</code> is FALSE, equivalent to <code>extent="normal"</code> . Overrides any <code>extent</code> argument. |
| ... | ... |

Value

a ggplot object

Author(s)

David Kahle <david@kahle.io>

See Also

[get_map\(\)](#), [qmap\(\)](#)

Examples

```
## Not run: ## map queries drag R CMD check

## extents and legends
#####
hdf <- get_map("houston, texas")
ggmap(hdf, extent = "normal")
ggmap(hdf) # extent = "panel", note qmap defaults to extent = "device"
ggmap(hdf, extent = "device")

# make some fake spatial data
mu <- c(-95.3632715, 29.7632836); nDataSets <- sample(4:10,1)
chkpts <- NULL
for(k in 1:nDataSets){
  a <- rnorm(2); b <- rnorm(2);
  si <- 1/3000 * (outer(a,a) + outer(b,b))
  chkpts <- rbind(
    chkpts,
    cbind(MASS::mvrnorm(rpois(1,50), jitter(mu, .01), si), k)
  )
}
chkpts <- data.frame(chkpts)
names(chkpts) <- c("lon", "lat", "class")
```

```

chkpts$class <- factor(chkpts$class)
qplot(lon, lat, data = chkpts, colour = class)

# show it on the map
ggmap(hdf, extent = "normal") +
  geom_point(aes(x = lon, y = lat, colour = class), data = chkpts, alpha = .5)

ggmap(hdf) +
  geom_point(aes(x = lon, y = lat, colour = class), data = chkpts, alpha = .5)

ggmap(hdf, extent = "device") +
  geom_point(aes(x = lon, y = lat, colour = class), data = chkpts, alpha = .5)

theme_set(theme_bw())
ggmap(hdf, extent = "device") +
  geom_point(aes(x = lon, y = lat, colour = class), data = chkpts, alpha = .5)

ggmap(hdf, extent = "device", legend = "topleft") +
  geom_point(aes(x = lon, y = lat, colour = class), data = chkpts, alpha = .5)

# qmplot is great for this kind of thing...
qmplot(lon, lat, data = chkpts, color = class, darken = .6)
qmplot(lon, lat, data = chkpts, geom = "density2d", color = class, darken = .6)

## maprange
#####

hdf <- get_map()
mu <- c(-95.3632715, 29.7632836)
points <- data.frame(MASS::mvrnorm(1000, mu = mu, diag(c(.1, .1))))
names(points) <- c("lon", "lat")
points$class <- sample(c("a","b"), 1000, replace = TRUE)

ggmap(hdf) + geom_point(data = points) # maprange built into extent = panel, device
ggmap(hdf) + geom_point(aes(colour = class), data = points)

ggmap(hdf, extent = "normal") + geom_point(data = points)
# note that the following is not the same as extent = panel
ggmap(hdf, extent = "normal", maprange = TRUE) + geom_point(data = points)

# and if you need your data to run off on a extent = device (legend included)
ggmap(hdf, extent = "normal", maprange = TRUE) +
  geom_point(aes(colour = class), data = points) +
  theme_nothing(legend = TRUE) + theme(legend.position = "right")

# again, qmplot is probably more useful
qmplot(lon, lat, data = points, color = class, darken = .4, alpha = I(.6))
qmplot(lon, lat, data = points, color = class, maptype = "stamen_toner_lite")

## cool examples
#####

# contour overlay

```

```

ggmap(get_map(mapytype = "satellite"), extent = "device") +
  stat_density2d(aes(x = lon, y = lat, colour = class), data = chkpts, bins = 5)

# adding additional content
library(grid)
baylor <- get_map("one bear place, waco, texas", zoom = 15, mapytype = "satellite")
ggmap(baylor)

# use gglocator to find lon/lat's of interest
(clicks <- gglocator(2) )
ggmap(baylor) +
  geom_point(aes(x = lon, y = lat), data = clicks, colour = "red", alpha = .5)
expand.grid(lon = clicks$lon, lat = clicks$lat)

ggmap(baylor) + theme_bw() +
  annotate("segment", x=-97.110, xend=-97.1188, y=31.5450, yend=31.5485,
  colour=I("red"), arrow = arrow(length=unit(0.3,"cm")), size = 1.5) +
  annotate("label", x=-97.113, y=31.5445, label = "Department of Statistical Science",
  colour = I("red"), size = 3.5) +
  labs(x = "Longitude", y = "Latitude") + ggtitle("Baylor University")

baylor <- get_map("marrs mclean science, waco, texas", zoom = 16, mapytype = "satellite")

ggmap(baylor, extent = "panel") +
  annotate("segment", x=-97.1175, xend=-97.1188, y=31.5449, yend=31.5485,
  colour=I("red"), arrow = arrow(length=unit(0.4,"cm")), size = 1.5) +
  annotate("label", x=-97.1175, y=31.5447, label = "Department of Statistical Science",
  colour = I("red"), size = 4)

# a shapefile like layer
data(zips)
ggmap(get_map(mapytype = "satellite", zoom = 8), extent = "device") +
  geom_polygon(aes(x = lon, y = lat, group = plotOrder),
  data = zips, colour = NA, fill = "red", alpha = .2) +
  geom_path(aes(x = lon, y = lat, group = plotOrder),
  data = zips, colour = "white", alpha = .4, size = .4)

library(plyr)
zipsLabels <- ddply(zips, .(zip), function(df){
  df[1,c("area", "perimeter", "zip", "lonCent", "latCent")]
})
ggmap(get_map(mapytype = "satellite", zoom = 9),
  extent = "device", legend = "none", darken = .5) +
  geom_text(aes(x = lonCent, y = latCent, label = zip, size = area),
  data = zipsLabels, colour = I("red")) +
  scale_size(range = c(1.5,6))

qplot(lonCent, latCent, data = zipsLabels, geom = "text",
  label = zip, size = area, mapytype = "stamen_toner_lite", color = I("red"))

```

```

)

## crime data example
#####

# only violent crimes
violent_crimes <- subset(crime,
  offense != "auto theft" &
  offense != "theft" &
  offense != "burglary"
)

# rank violent crimes
violent_crimes$offense <-
  factor(violent_crimes$offense,
    levels = c("robbery", "aggravated assault",
      "rape", "murder")
  )

# restrict to downtown
violent_crimes <- subset(violent_crimes,
  -95.39681 <= lon & lon <= -95.34188 &
  29.73631 <= lat & lat <= 29.78400
)

# get map and bounding box
theme_set(theme_bw(16))
HoustonMap <- qmap("houston", zoom = 14, color = "bw",
  extent = "device", legend = "topleft")
HoustonMap <- ggmap(
  get_map("houston", zoom = 14, color = "bw"),
  extent = "device", legend = "topleft"
)

# the bubble chart
HoustonMap +
  geom_point(aes(x = lon, y = lat, colour = offense, size = offense), data = violent_crimes) +
  scale_colour_discrete("Offense", labels = c("Robbery", "Aggravated Assault", "Rape", "Murder")) +
  scale_size_discrete("Offense", labels = c("Robbery", "Aggravated Assault", "Rape", "Murder"),
    range = c(1.75,6)) +
  guides(size = guide_legend(override.aes = list(size = 6))) +
  theme(
    legend.key.size = grid::unit(1.8, "lines"),
    legend.title = element_text(size = 16, face = "bold"),
    legend.text = element_text(size = 14)
  ) +
  labs(colour = "Offense", size = "Offense")

# doing it with qmplot is even easier
qmplot(lon, lat, data = violent_crimes, maptype = "stamen_toner_lite",

```

```

    color = offense, size = offense, legend = "topleft"
  )

# or, with styling:
qplot(lon, lat, data = violent_crimes, maptype = "stamen_toner_lite",
  color = offense, size = offense, legend = "topleft"
) +
scale_colour_discrete("Offense", labels = c("Robbery", "Aggravated Assault", "Rape", "Murder")) +
scale_size_discrete("Offense", labels = c("Robbery", "Aggravated Assault", "Rape", "Murder"),
  range = c(1.75, 6)) +
guides(size = guide_legend(override.aes = list(size = 6))) +
theme(
  legend.key.size = grid::unit(1.8, "lines"),
  legend.title = element_text(size = 16, face = "bold"),
  legend.text = element_text(size = 14)
) +
labs(colour = "Offense", size = "Offense")

# a contour plot
HoustonMap +
  stat_density2d(aes(x = lon, y = lat, colour = offense),
    size = 3, bins = 2, alpha = 3/4, data = violent_crimes) +
  scale_colour_discrete("Offense", labels = c("Robbery", "Aggravated Assault", "Rape", "Murder")) +
  theme(
    legend.text = element_text(size = 15, vjust = .5),
    legend.title = element_text(size = 15, face = "bold"),
    legend.key.size = grid::unit(1.8, "lines")
  )

# 2d histogram...
HoustonMap +
  stat_bin_2d(aes(x = lon, y = lat, colour = offense, fill = offense),
    size = .5, bins = 30, alpha = 2/4, data = violent_crimes) +
  scale_colour_discrete("Offense",
    labels = c("Robbery", "Aggravated Assault", "Rape", "Murder"),
    guide = FALSE) +
  scale_fill_discrete("Offense", labels = c("Robbery", "Aggravated Assault", "Rape", "Murder")) +
  theme(
    legend.text = element_text(size = 15, vjust = .5),
    legend.title = element_text(size = 15, face = "bold"),
    legend.key.size = grid::unit(1.8, "lines")
  )

```



```

# changing gears (get a color map)
houston <- get_map("houston", zoom = 14)
HoustonMap <- ggmap(houston, extent = "device", legend = "topleft")

# a filled contour plot...
HoustonMap +
  stat_density2d(aes(x = lon, y = lat, fill = ..level.., alpha = ..level..),
    size = 2, bins = 4, data = violent_crimes, geom = "polygon") +
  scale_fill_gradient("Violent\nCrime\nDensity") +
  scale_alpha(range = c(.4, .75), guide = FALSE) +
  guides(fill = guide_colorbar(barwidth = 1.5, barheight = 10))

# ... with an insert

overlay <- stat_density2d(aes(x = lon, y = lat, fill = ..level.., alpha = ..level..),
  bins = 4, geom = "polygon", data = violent_crimes)

attr(houston,"bb") # to help finding (x/y)(min/max) vals below

HoustonMap +
  stat_density2d(aes(x = lon, y = lat, fill = ..level.., alpha = ..level..),
    bins = 4, geom = "polygon", data = violent_crimes) +
  scale_fill_gradient("Violent\nCrime\nDensity") +
  scale_alpha(range = c(.4, .75), guide = FALSE) +
  guides(fill = guide_colorbar(barwidth = 1.5, barheight = 10)) +
  inset(
    grob = ggplotGrob(ggplot() + overlay +
      scale_fill_gradient("Violent\nCrime\nDensity") +
      scale_alpha(range = c(.4, .75), guide = FALSE) +
      theme_inset()
    ),
    xmin = -95.35877, xmax = -95.34229,
    ymin = 29.73754, ymax = 29.75185
  )

## more examples
#####

# you can layer anything on top of the maps (even meaningless stuff)
df <- data.frame(
  lon = rep(seq(-95.39, -95.35, length.out = 8), each = 20),
  lat = sapply(
    rep(seq(29.74, 29.78, length.out = 8), each = 20),
    function(x) rnorm(1, x, .002)
  )
)

```

```

    ),
    class = rep(letters[1:8], each = 20)
  )

  qplot(lon, lat, data = df, geom = "boxplot", fill = class)

HoustonMap +
  geom_boxplot(aes(x = lon, y = lat, fill = class), data = df)

## the base_layer argument - faceting
#####

df <- data.frame(
  x = rnorm(1000, -95.36258, .2),
  y = rnorm(1000, 29.76196, .2)
)

# no apparent change because ggmap sets maprange = TRUE with extent = "panel"
ggmap(get_map(), base_layer = ggplot(aes(x = x, y = y), data = df)) +
  geom_point(colour = "red")

# ... but there is a difference
ggmap(get_map(), base_layer = ggplot(aes(x = x, y = y), data = df), extent = "normal") +
  geom_point(colour = "red")

# maprange can fix it (so can extent = "panel")
ggmap(get_map(), maprange = TRUE, extent = "normal",
  base_layer = ggplot(aes(x = x, y = y), data = df)) +
  geom_point(colour = "red")

# base_layer makes faceting possible
df <- data.frame(
  x = rnorm(10*100, -95.36258, .075),
  y = rnorm(10*100, 29.76196, .075),
  year = rep(paste("year", format(1:10)), each = 100)
)
ggmap(get_map(), base_layer = ggplot(aes(x = x, y = y), data = df)) +
  geom_point() + facet_wrap(~ year)

ggmap(get_map(), base_layer = ggplot(aes(x = x, y = y), data = df), extent = "device") +
  geom_point() + facet_wrap(~ year)

qplot(x, y, data = df)
qplot(x, y, data = df, facets = ~ year)

## neat faceting examples
#####

# simulated example

```

```

df <- data.frame(
  x = rnorm(10*100, -95.36258, .05),
  y = rnorm(10*100, 29.76196, .05),
  year = rep(paste("year",format(1:10)), each = 100)
)
for(k in 0:9){
  df$x[1:100 + 100*k] <- df$x[1:100 + 100*k] + sqrt(.05)*cos(2*pi*k/10)
  df$y[1:100 + 100*k] <- df$y[1:100 + 100*k] + sqrt(.05)*sin(2*pi*k/10)
}

ggmap(get_map(),
  base_layer = ggplot(aes(x = x, y = y), data = df)) +
  stat_density2d(aes(fill = ..level.., alpha = ..level..),
    bins = 4, geom = "polygon") +
  scale_fill_gradient2(low = "white", mid = "orange", high = "red", midpoint = 10) +
  scale_alpha(range = c(.2, .75), guide = FALSE) +
  facet_wrap(~ year)

# crime example by month
levels(violent_crimes$month) <- paste(
  toupper(substr(levels(violent_crimes$month),1,1)),
  substr(levels(violent_crimes$month),2,20), sep = ""
)
houston <- get_map(location = "houston", zoom = 14, source = "osm", color = "bw")
HoustonMap <- ggmap(houston,
  base_layer = ggplot(aes(x = lon, y = lat), data = violent_crimes)
)

HoustonMap +
  stat_density2d(aes(x = lon, y = lat, fill = ..level.., alpha = ..level..),
    bins = I(5), geom = "polygon", data = violent_crimes) +
  scale_fill_gradient2("Violent\nCrime\nDensity",
    low = "white", mid = "orange", high = "red", midpoint = 500) +
  labs(x = "Longitude", y = "Latitude") + facet_wrap(~ month) +
  scale_alpha(range = c(.2, .55), guide = FALSE) +
  ggtitle("Violent Crime Contour Map of Downtown Houston by Month") +
  guides(fill = guide_colorbar(barwidth = 1.5, barheight = 10))

## darken argument
#####
ggmap(get_map())
ggmap(get_map(), darken = .5)
ggmap(get_map(), darken = c(.5,"white"))
ggmap(get_map(), darken = c(.5,"red")) # silly, but possible

```

```
## End(Not run)
```

| | |
|---------------|--------------------------------|
| ggmap-defunct | <i>Defunct ggmap functions</i> |
|---------------|--------------------------------|

Description

As provider services change over time, ggmap has to make corresponding changes. Since its inception, a few services have stopped offering their previous functionality, and in some cases this has required us to remove those functions from the package entirely.

Details

The following are defunct ggmap functions:

- `get_cloudeamap`
- `get_navermap`
- `get_openstreetmap`
- `get_stamenmap`

| | |
|-----------|--|
| ggmapplot | <i>Don't use this function, use ggmap.</i> |
|-----------|--|

Description

ggmap plots the raster object produced by `get_map()`.

Usage

```
ggmapplot(  
  ggmap,  
  fullpage = FALSE,  
  base_layer,  
  maprange = FALSE,  
  expand = FALSE,  
  ...  
)
```

Arguments

| | |
|------------|---|
| ggmap | an object of class ggmap (from function get_map()) |
| fullpage | logical; should the map take up the entire viewport? |
| base_layer | a ggplot(aes(...), ...) call; see examples |
| maprange | logical for use with base_layer; should the map define the x and y limits? |
| expand | should the map extend to the edge of the panel? used with base_layer and maprange=TRUE. |
| ... | ... |

Value

a ggplot object

Author(s)

David Kahle <david@kahle.io>

See Also

[get_map\(\)](#), [qmap\(\)](#)

Examples

```
## Not run:
this is a deprecated function, use ggmap.

## End(Not run)
```

ggmap_options

ggmap Options

Description

ggmap stores options as a named list in R's global options, i.e. `getOption("ggmap")`. It currently stores two such options, one for Google credentialing and one to suppress private API information in the URLs printed to the screen when web queries are placed. For both of those, see [register_google\(\)](#).

Usage

```
set_ggmap_option(...)
```

```
has_ggmap_options()
```

```
has_ggmap_option(option)
```

```
ggmap_credentials()
```

Arguments

... a named listing of options to set
 option a specific option to query, e.g. "display_api_key"

Author(s)

David Kahle <david@kahle.io>

See Also

[register_google\(\)](#)

Examples

```
getOption("ggmap")
has_ggmap_options()
has_ggmap_option("display_api_key")
```

hadley

Highly unofficial ggplot2 image

Description

Highly unofficial ggplot2 image

Author(s)

Garrett Golemund <golemund@gmail.com>

inset

Add ggplot2 insets to a map

Description

This is identical to `ggplot2::annotation_custom` for use with `ggmap`

Usage

```
inset(grob, xmin = -Inf, xmax = Inf, ymin = -Inf, ymax = Inf)
```

Arguments

| | |
|------------|---|
| grob | grob to display |
| xmin, xmax | x location (in data coordinates) giving horizontal location of raster |
| ymin, ymax | y location (in data coordinates) giving vertical location of raster |

Details

Most useful for adding tables, inset plots, and other grid-based decorations

Note

[annotation_custom\(\)](#) expects the grob to fill the entire viewport defined by xmin, xmax, ymin, ymax. Grobs with a different (absolute) size will be center-justified in that region. Inf values can be used to fill the full plot panel

| | |
|--------------|--|
| inset_raster | <i>Create a (ggplot2) raster layer</i> |
|--------------|--|

Description

This is a special version of `ggplot2::annotation_raster` for use with `ggmap`. (It simply removes the requirement for cartesian coordinates.) The only difference between [inset_raster\(\)](#) and [inset_ggmap\(\)](#) is their arguments. [inset_ggmap\(\)](#) is simply a wrapper of [inset_raster\(\)](#) with `xmin, ..., ymax` arguments equal to the map's bounding box.

Usage

```
inset_raster(raster, xmin, xmax, ymin, ymax, interpolate = TRUE)

inset_ggmap(ggmap)
```

Arguments

| | |
|-------------|---|
| raster | raster object to display |
| xmin, xmax | x location (in data coordinates) giving horizontal location of raster |
| ymin, ymax | y location (in data coordinates) giving vertical location of raster |
| interpolate | interpolate the raster? (i.e. antialiasing) |
| ggmap | a ggmap object, see get_map() |

See Also

[bb2bbox\(\)](#)

Examples

```
## Not run: # save cran check time

bbox <- c(left = -97.1268, bottom = 31.536245, right = -97.099334, top = 31.559652)

terrain_map <- get_stadiamap(bbox, zoom = 14, maptype = "stamen_terrain_background", color = "bw")
ggmap(terrain_map)

lines_map <- get_stadiamap(bbox, zoom = 14, maptype = "stamen_toner_lines")
ggmap(lines_map)

ggmap(terrain_map) +
  inset_ggmap(lines_map)

## End(Not run)
```

legs2route

Convert a leg-structured route to a route-structured route

Description

Convert a leg-structured route to a route-structured route

Usage

```
legs2route(legsdf)
```

Arguments

legsdf a legs-structured route, see [route\(\)](#)

See Also

[geom_path\(\)](#)

Examples

```
## Not run: requires Google API key, see ?register_google

(legs_df <- route("houston", "galveston"))
legs2route(legs_df)

(legs_df <- route(
  "marrs mclean science, baylor university",
  "220 south 3rd street, waco, tx 76701", # ninfa"s
```



```
alternatives = TRUE))

legs2route(legs_df)

from <- "houston, texas"
to <- "waco, texas"
legs_df <- route(from, to)

qmap("college station, texas", zoom = 8) +
  geom_segment(
    aes(x = start_lon, y = start_lat, xend = end_lon, yend = end_lat),
    colour = "red", size = 1.5, data = legs_df
  )
# notice boxy ends

qmap("college station, texas", zoom = 8) +
  geom_leg(
    aes(x = start_lon, y = start_lat, xend = end_lon, yend = end_lat),
    colour = "red", size = 1.5, data = legs_df
  )
# notice overshooting ends

route_df <- legs2route(legs_df)
qmap("college station, texas", zoom = 8) +
  geom_path(
    aes(x = lon, y = lat),
    colour = "red", size = 1.5, data = route_df, lineend = "round"
  )

## End(Not run)
```

Description

Convert a lon/lat coordinate to a tile coordinate for a given zoom. Decimal tile coordinates (x, y) are reported.

Usage

```
LonLat2XY(lon_deg, lat_deg, zoom, xpix = 256, ypix = 256)
```

Arguments

| | |
|---------|--------------------------|
| lon_deg | longitude in degrees |
| lat_deg | latitude in degrees |
| zoom | zoom |
| xpix | width of tile in pixels |
| ypix | length of tile in pixels |

Value

a data frame with columns X, Y, x, y

Author(s)

David Kahle <david@kahle.io>, based on RgoogleMaps::LatLon2XY() by Markus Loecher of Sense Networks <markus@sensenetworks.com>

See Also

https://wiki.openstreetmap.org/wiki/Slippy_map_tilenames

Examples

```
## Not run:  
gc <- geocode('baylor university')  
LonLat2XY(gc$lon, gc$lat, 10)  
  
## End(Not run)
```

make_bbox

Compute a bounding box

Description

Compute a bounding box for a given longitude / latitude collection.

Usage

```
make_bbox(lon, lat, data, f = 0.05)
```

Arguments

| | |
|------|---|
| lon | longitude |
| lat | latitude |
| data | (optional) a data frame containing lon and lat as variables |
| f | number specifying the fraction by which the range should be extended. if length 2 vector, applies to longitude and then latitude. |

Examples

```
make_bbox(lon, lat, data = crime)
make_bbox(lon, lat, data = crime, f = .20)
make_bbox(lon, lat, data = crime, f = c(.20, .05))

(lon <- sample(crime$lon, 10))
(lat <- sample(crime$lat, 10))
make_bbox(lon, lat)
make_bbox(lon, lat, f = .10) # bigger box
```

mapdist

Compute map distances using Google

Description

Compute map distances using Google's Distance Matrix API. Note: To use Google's Distance Matrix API, you must first enable the API in the Google Cloud Platform Console. See [register_google\(\)](#).

Usage

```
mapdist(
  from,
  to,
  mode = c("driving", "walking", "bicycling", "transit"),
  output = c("simple", "all"),
  urlonly = FALSE,
  override_limit = FALSE,
  ext = "com",
  inject = "",
  ...
)

distQueryCheck()
```

Arguments

| | |
|----------------|--|
| from | name of origin addresses in a data frame (vector accepted), or a data frame with from and to columns |
| to | name of destination addresses in a data frame (vector accepted) |
| mode | driving, bicycling, walking, or transit |
| output | amount of output |
| urlonly | return only the url? |
| override_limit | override the current query count (.google_distance_query_times) |
| ext | top level domain domain extension (e.g. "com", "co.nz") |
| inject | character string to add to the url |
| ... | ... |

Details

if parameters from and to are specified as geographic coordinates, they are reverse geocoded with revgeocode. note that the google maps api limits to 2500 element queries a day.

Value

a data frame (output="simple") or all of the geocoded information (output="all")

Author(s)

David Kahle <david@kahle.io>

See Also

<https://developers.google.com/maps/documentation/distance-matrix/>, <https://developers.google.com/maps/documentation/distance-matrix/overview/>

Examples

```
## Not run:  requires Google API key, see ?register_google

## basic usage
#####

mapdist("waco, texas", "houston, texas")

# many from, single to
from <- c("houston, texas", "dallas")
to <- "waco, texas"
mapdist(from, to)
mapdist(from, to, mode = "bicycling")
mapdist(from, to, mode = "walking")
```

```

# tibble of from's, vector of to's
# (with a data frame, remember stringsAsFactors = FALSE)
tibble(
  "from" = c("houston", "houston", "dallas"),
  "to" = c("waco", "san antonio", "houston")
) %>% mapdist()

# distance matrix
library("tidyverse")
c("Hamburg, Germany", "Stockholm, Sweden", "Copenhagen, Denmark") %>%
  list(., .) %>%
  set_names(c("from", "to")) %>%
  cross_df() %>%
  mapdist() -> distances

distances

distances %>%
  select(from, to, km) %>%
  spread(from, km)

## other examples
#####

# many from, single to with addresses
from <- c(
  "1600 Amphitheatre Parkway, Mountain View, CA",
  "3111 World Drive Walt Disney World, Orlando, FL"
)
to <- "1600 Pennsylvania Avenue, Washington DC"
mapdist(from, to)

# mode = "transit"
from <- "st lukes hospital houston texas"
to <- "houston zoo, houston texas"
mapdist(from, to, mode = "transit")

## geographic coordinates are accepted as well
#####
(wh <- as.numeric(geocode("the white house, dc"))))
(lm <- as.numeric(geocode("lincoln memorial washington dc")))
mapdist(wh, lm, mode = "walking")

```

```
## End(Not run)
```

| | |
|------------------|--|
| OSM_scale_lookup | <i>Look up OpenStreetMap scale for a given zoom level.</i> |
|------------------|--|

Description

Look up OpenStreetMap scale for a given zoom level.

Usage

```
OSM_scale_lookup(zoom = 10)
```

Arguments

| | |
|------|-------------|
| zoom | google zoom |
|------|-------------|

Details

The calculation of an appropriate OSM scale value for a given zoom level is a complicated task. For details, see <https://wiki.openstreetmap.org/wiki/FAQ>

Value

scale

Author(s)

David Kahle <david@kahle.io>

Examples

```
OSM_scale_lookup(zoom = 3)
OSM_scale_lookup(zoom = 10)

## Not run:
# these can take a long time or are prone to crashing
# if the osm server load is too high

# these maps are were the ones used to tailor fit the scale
# the zooms were fixed
ggmap(get_map(zoom = 3, source = 'osm', scale = 47500000), extent = "device")
ggmap(get_map(zoom = 4, source = 'osm', scale = 32500000), extent = "device")
ggmap(get_map(zoom = 5, source = 'osm', scale = 15000000), extent = "device")
ggmap(get_map(zoom = 6, source = 'osm', scale = 10000000), extent = "device")
ggmap(get_map(zoom = 7, source = 'osm', scale = 5000000), extent = "device")
ggmap(get_map(zoom = 8, source = 'osm', scale = 2800000), extent = "device")
ggmap(get_map(zoom = 9, source = 'osm', scale = 1200000), extent = "device")
```

```
ggmap(get_map(zoom = 10, source = 'osm', scale = 575000), extent = "device")
ggmap(get_map(zoom = 11, source = 'osm', scale = 220000), extent = "device")
ggmap(get_map(zoom = 12, source = 'osm', scale = 110000), extent = "device")
ggmap(get_map(zoom = 13, source = 'osm', scale = 70000), extent = "device")
ggmap(get_map(zoom = 14, source = 'osm', scale = 31000), extent = "device")
ggmap(get_map(zoom = 15, source = 'osm', scale = 15000), extent = "device")
ggmap(get_map(zoom = 16, source = 'osm', scale = 7500), extent = "device")
ggmap(get_map(zoom = 17, source = 'osm', scale = 4000), extent = "device")
ggmap(get_map(zoom = 18, source = 'osm', scale = 2500), extent = "device")
ggmap(get_map(zoom = 19, source = 'osm', scale = 1750), extent = "device")
ggmap(get_map(zoom = 20, source = 'osm', scale = 1000), extent = "device")

# the USA
lonR <- c(1.01, .99)*c(-124.73, -66.95)
latR <- c(.99, 1.01)*c(24.52, 49.38)
qmap(lonR = lonR, latR = latR, source = 'osm', scale = 325E5)

## End(Not run)
```

print.ggmap

Print a map

Description

Print a console description of a map

Usage

```
## S3 method for class 'ggmap'
print(x, ...)
```

Arguments

x an object of class `ggmap`
... additional parameters

Value

Invisibly returns `x`.

Examples

```
## Not run: requires a Stadia Maps API key. see ?register_stadiamaps
get_stadiamap(zoom = 9)
```

```
## End(Not run)
```

qmap

Quick map plot

Description

qmap is a wrapper for [ggmap\(\)](#) and [get_map\(\)](#).

Usage

```
qmap(location = "houston", ...)
```

Arguments

| | |
|----------|--|
| location | character; location of interest |
| ... | stuff to pass to ggmap() and get_map() |

Value

a ggplot object

Author(s)

David Kahle <david@kahle.io>

See Also

[ggmap\(\)](#) and [get_map\(\)](#)

Examples

```
## Not run: some requires Google API key; heavy network/time load

location <- "marrs mclean science, waco, texas"
qmap(location)
qmap(location, zoom = 14)
qmap(location, zoom = 14, source = "osm")
qmap(location, zoom = 14, source = "osm", scale = 20000)
qmap(location, zoom = 14, maptype = "satellite")
qmap(location, zoom = 14, maptype = "hybrid")
qmap(location, zoom = 14, maptype = "stamen_toner", source = "stadia")
qmap(location, zoom = 14, maptype = "stamen_watercolor", source = "stadia")
qmap(location, zoom = 14, maptype = "stamen_terrain_background", source = "stadia")
qmap(location, zoom = 14, maptype = "stamen_toner_lite", source = "stadia")

where <- "the white house, washington dc"
```



```
wh <- geocode(wh)
qmap(wh, maprange = TRUE, zoom = 15,
     base_layer = ggplot(aes(x=lon, y=lat), data = wh)) +
  geom_point()

## End(Not run)
```

qmpplot

Quick map plot

Description

`qmpplot()` is the `ggmap` equivalent to the `ggplot2` function `qplot` and allows for the quick plotting of maps with data/models/etc.

Usage

```
qmpplot(
  x,
  y,
  ...,
  data,
  zoom,
  source = "stadia",
  maptype = "stamen_toner_lite",
  extent = "device",
  legend = "right",
  padding = 0.02,
  force = FALSE,
  darken = c(0, "black"),
  mapcolor = "color",
  facets = NULL,
  margins = FALSE,
  geom = "auto",
  stat = list(NULL),
  position = list(NULL),
  xlim = c(NA, NA),
  ylim = c(NA, NA),
  main = NULL,
  f = 0.05,
  xlab = "Longitude",
  ylab = "Latitude"
)
```

Arguments

| | |
|----------|--|
| x | longitude values |
| y | latitude values |
| ... | other aesthetics passed for each layer |
| data | data frame to use (optional). If not specified, will create one, extracting vectors from the current environment. |
| zoom | map zoom, see get_map() |
| source | map source, see get_map() |
| maptype | map type, see get_map() |
| extent | how much of the plot should the map take up? "normal", "panel", or "device" (default) |
| legend | "left", "right" (default), "bottom", "top", "bottomleft", "bottomright", "topleft", "topright", "none" (used with extent = "device") |
| padding | distance from legend to corner of the plot (used with extent = "device") |
| force | force new map (don't use archived version) |
| darken | vector of the form <code>c(number, color)</code> , where number is in (0,1) and color is a character string indicating the color of the darken. 0 indicates no darkening, 1 indicates a black-out. |
| mapcolor | color ("color") or black-and-white ("bw") |
| facets | faceting formula to use. Picks facet_wrap() or facet_grid() depending on whether the formula is one sided or two-sided |
| margins | whether or not margins will be displayed |
| geom | character vector specifying geom to use. defaults to "point" |
| stat | character vector specifying statistics to use |
| position | character vector giving position adjustment to use |
| xlim | limits for x axis |
| ylim | limits for y axis |
| main | character vector or expression for plot title |
| f | number specifying the fraction by which the range should be extended |
| xlab | character vector or expression for x axis label |
| ylab | character vector or expression for y axis label |

Examples

```
## Not run: # these are skipped to conserve R check time
```

```
qmpplot(lon, lat, data = crime)
```

```
# only violent crimes
violent_crimes <- subset(crime,
  offense != "auto theft" &
```

```

    offense != "theft" &
    offense != "burglary"
  )

# rank violent crimes
violent_crimes$offense <- factor(
  violent_crimes$offense,
  levels = c("robbery", "aggravated assault", "rape", "murder")
)

# restrict to downtown
violent_crimes <- subset(violent_crimes,
  -95.39681 <= lon & lon <= -95.34188 &
  29.73631 <= lat & lat <= 29.78400
)

theme_set(theme_bw())

qplot(lon, lat, data = violent_crimes, colour = offense,
  size = I(3.5), alpha = I(.6), legend = "topleft")

qplot(lon, lat, data = violent_crimes, geom = c("point", "density2d"))
qplot(lon, lat, data = violent_crimes) + facet_wrap(~ offense)
qplot(lon, lat, data = violent_crimes, extent = "panel") + facet_wrap(~ offense)
qplot(lon, lat, data = violent_crimes, extent = "panel", colour = offense, darken = .4) +
  facet_wrap(~ month)

qplot(long, lat, xend = long + delta_long,
  color = I("red"), yend = lat + delta_lat, data = seals,
  geom = "segment", zoom = 5)

qplot(long, lat, xend = long + delta_long, maptype = "stamen_watercolor",
  yend = lat + delta_lat, data = seals,
  geom = "segment", zoom = 6)

qplot(long, lat, xend = long + delta_long, maptype = "stamen_terrain",
  yend = lat + delta_lat, data = seals,
  geom = "segment", zoom = 6)

qplot(lon, lat, data = wind, size = I(.5), alpha = I(.5)) +
  ggtitle("NOAA Wind Report Sites")

# thin down data set...
s <- seq(1, 227, 8)
thinwind <- subset(wind,
  lon %in% unique(wind$lon)[s] &
  lat %in% unique(wind$lat)[s]
)

```

```

# for some reason adding arrows to the following plot bugs
theme_set(theme_bw(18))

qmpplot(lon, lat, data = thinwind, geom = "tile", fill = spd, alpha = spd,
  legend = "bottomleft") +
  geom_leg(aes(xend = lon + delta_lon, yend = lat + delta_lat)) +
  scale_fill_gradient2("Wind Speed\nand\nDirection",
    low = "green", mid = scales::muted("green"), high = "red") +
  scale_alpha("Wind Speed\nand\nDirection", range = c(.1, .75)) +
  guides(fill = guide_legend(), alpha = guide_legend())

## kriging
#####
# the below examples show kriging based on undeclared packages
# to better comply with CRAN's standards, we remove it from
# executing, but leave the code as a kind of case-study
# they also require the rgdal library

library(lattice)
library(sp)
library(rgdal)

# load in and format the meuse dataset (see bivand, pebesma, and gomez-rubio)
data(meuse)
coordinates(meuse) <- c("x", "y")
proj4string(meuse) <- CRS("+init=epsg:28992")
meuse <- spTransform(meuse, CRS("+proj=longlat +datum=WGS84"))

# plot
plot(meuse)

m <- data.frame(slot(meuse, "coords"), slot(meuse, "data"))
names(m)[1:2] <- c("lon", "lat")

qmpplot(lon, lat, data = m)
qmpplot(lon, lat, data = m, zoom = 14)

qmpplot(lon, lat, data = m, size = zinc,
  zoom = 14, source = "google", maptype = "satellite",
  alpha = I(.75), color = I("green"),
  legend = "topleft", darken = .2
) + scale_size("Zinc (ppm)")

```

```
# load in the meuse.grid dataset (looking toward kriging)
library(gstat)
data(meuse.grid)
coordinates(meuse.grid) <- c("x", "y")
proj4string(meuse.grid) <- CRS("+init=epsg:28992")
meuse.grid <- spTransform(meuse.grid, CRS("+proj=longlat +datum=WGS84"))

# plot it
plot(meuse.grid)

mg <- data.frame(slot(meuse.grid, "coords"), slot(meuse.grid, "data"))
names(mg)[1:2] <- c("lon", "lat")

qmpplot(lon, lat, data = mg, shape = I(15), zoom = 14, legend = "topleft") +
  geom_point(aes(size = zinc), data = m, color = "green") +
  scale_size("Zinc (ppm)")

# interpolate at unobserved locations (i.e. at meuse.grid points)
# pre-define scale for consistency
scale <- scale_color_gradient("Predicted\nZinc (ppm)",
  low = "green", high = "red", lim = c(100, 1850)
)

# inverse distance weighting
idw <- idw(log(zinc) ~ 1, meuse, meuse.grid, idp = 2.5)
mg$idw <- exp(slot(idw, "data")$var1.pred)

qmpplot(lon, lat, data = mg, shape = I(15), color = idw,
  zoom = 14, legend = "topleft", alpha = I(.75), darken = .4
) + scale

# linear regression
lin <- krige(log(zinc) ~ 1, meuse, meuse.grid, degree = 1)
mg$lin <- exp(slot(lin, "data")$var1.pred)

qmpplot(lon, lat, data = mg, shape = I(15), color = lin,
  zoom = 14, legend = "topleft", alpha = I(.75), darken = .4
) + scale

# trend surface analysis
tsa <- krige(log(zinc) ~ 1, meuse, meuse.grid, degree = 2)
mg$tsa <- exp(slot(tsa, "data")$var1.pred)
```

```

qmplot(lon, lat, data = mg, shape = I(15), color = tsa,
        zoom = 14, legend = "topleft", alpha = I(.75), darken = .4
) + scale

# ordinary kriging
vgram <- variogram(log(zinc) ~ 1, meuse) # plot(vgram)
vgramFit <- fit.variogram(vgram, vgm(1, "Exp", .2, .1))
ordKrige <- krige(log(zinc) ~ 1, meuse, meuse.grid, vgramFit)
mg$ordKrige <- exp(slot(ordKrige, "data")$var1.pred)

qmplot(lon, lat, data = mg, shape = I(15), color = ordKrige,
        zoom = 14, legend = "topleft", alpha = I(.75), darken = .4
) + scale

# universal kriging
vgram <- variogram(log(zinc) ~ 1, meuse) # plot(vgram)
vgramFit <- fit.variogram(vgram, vgm(1, "Exp", .2, .1))
univKrige <- krige(log(zinc) ~ sqrt(dist), meuse, meuse.grid, vgramFit)
mg$univKrige <- exp(slot(univKrige, "data")$var1.pred)

qmplot(lon, lat, data = mg, shape = I(15), color = univKrige,
        zoom = 14, legend = "topleft", alpha = I(.75), darken = .4
) + scale

# adding observed data layer
qmplot(lon, lat, data = mg, shape = I(15), color = univKrige,
        zoom = 14, legend = "topleft", alpha = I(.75), darken = .4
) +
  geom_point(
    aes(x = lon, y = lat, size = zinc),
    data = m, shape = 1, color = "black"
) +
  scale +
  scale_size("Observed\nLog Zinc")

## End(Not run) # end dontrun

```

Description

This page contains documentation for tools related to enabling Google services in R. See the Details section of this file for background information.

Usage

```
showing_key()

ggmap_show_api_key()

ggmap_hide_api_key()

scrub_key(string, with = "xxx")

register_google(
  key,
  account_type,
  client,
  signature,
  second_limit,
  day_limit,
  write = FALSE
)

## S3 method for class 'google_credentials'
print(x, ...)

google_key()

has_google_key()

has_google_account()

google_account()

google_client()

has_google_client()

google_signature()

has_google_signature()

google_second_limit()

google_day_limit()
```

Arguments

| | |
|--------------|---|
| string | a url string to be scrubbed. currently key, signature, and client keywords are scrubbed from the url and replace with the with argument |
| with | a string to replace |
| key | an api key |
| account_type | "standard" or "premium" |
| client | client code |
| signature | signature code |
| second_limit | query limit per second (default 50) |
| day_limit | query limit per day (default 2500 for standard accounts, 100000 for premium accounts) |
| write | if TRUE, stores the secrets provided in the .Renviron file |
| x | a google credentials class object |
| ... | a dumped formal argument to the generic print method |

Details

As of mid-2018, the Google Maps Platform requires a registered API key. While this alleviates previous burdens (e.g. query limits), it creates some challenges as well. The most immediate challenge for most R users is that ggmmap functions that use Google's services no longer function out of the box, since the user has to setup an account with Google, enable the relevant APIs, and then tell R about the user's setup.

To obtain an API key and enable services, go to <https://mapsplatform.google.com/>. This documentation shows you how to input the requisite information (e.g. your API key) into R, and it also shows you a few tools that can help you work with the credentialing.

To tell ggmmap about your API key, use `register_google()`, e.g. `register_google(key = "mQkzTpiaLYjPqXQBotesgif3E")` (that's a fake key). This will set your API key for the current session, but if you restart R, you'll need to do it again. You can set it permanently by setting `write = TRUE`, see the examples. If you set it permanently it will be stored in your .Renviron file, and that will be accessed by ggmmap persistently across sessions.

Users should be aware that the API key, a string of jarbled characters/numbers/symbols, is a PRIVATE key - it uniquely identifies and authenticates you to Google's services. If anyone gets your API key, they can use it to masquerade as you to Google and potentially use services that you have enabled. Since Google requires a valid credit card to use its online cloud services, this also means that anyone who obtains your key can potentially make charges to your card in the form of Google services. So be sure to not share your API key. To mitigate against users inadvertently sharing their keys, by default ggmmap never displays a user's key in messages displayed to the console.

Users should also be aware that ggmmap has no mechanism with which to safeguard the private key once registered with R. That is to say, once you register your API key, any function R will have access to it. As a consequence, ggmmap will not know if another function, potentially from a compromised package, accesses the key and uploads it to a third party. For this reason, when using ggmmap we recommend a heightened sense of security and self-awareness: only use trusted packages, do not save API keys in script files, routinely cycle keys (regenerate new keys and retire old ones), etc. Google offers features to help in securing your API key, including things like limiting queries

using that key to a particular IP address, as well as guidance on security best practices. See https://cloud.google.com/docs/authentication/api-keys#securing_an_api_key for details.

Author(s)

David Kahle <david@kahle.io>

See Also

<https://mapsplatform.google.com/>, <https://developers.google.com/maps/documentation/maps-static/get-api-key/>, <https://developers.google.com/maps/documentation/maps-static/usage-and-billing/>

Examples

```
# this sets your google map for this session
# register_google(key = "[your key]")

# this sets your google map permanently
# register_google(key = "[your key]", write = TRUE)

has_google_key()
google_key()
has_google_client()
has_google_signature()

geocode("waco, texas", urlonly = TRUE)
ggmap_show_api_key()
geocode("waco, texas", urlonly = TRUE)
ggmap_hide_api_key()
geocode("waco, texas", urlonly = TRUE)

scrub_key("key=d_5iD")
scrub_key("key=d_5iD", "[your \\1]")
scrub_key("signature=d_5iD")
scrub_key("client=a_5sS&signature=d_5iD")
```

register_stadiamaps *Register a Stadia Maps API Key*

Description

This page contains documentation for tools related to enabling Stadia Maps services in R. See the Details section of this file for background information.

Usage

```
register_stadiamaps(key, write = FALSE)
```

```
stadiamaps_key()
```

```
has_stadiamaps_key()
```

Arguments

| | |
|-------|--|
| key | an api key |
| write | if TRUE, stores the secrets provided in the .Renviron file |

Details

To obtain an API key and enable services, go to <https://client.stadiamaps.com/signup/>. It is completely free for non-commercial and evaluation use (a license is for commercial use; see <https://stadiamaps.com/pricing> for pricing), and no credit card is required to sign up.

To tell ggmap about your API key, use `register_stadiamaps()`, e.g. `register_stadiamaps(key = "YOUR-API-KEY")` (that's a fake key). This will set your API key for the current session, but if you restart R, you'll need to do it again. You can set it permanently by setting `write = TRUE`, see the examples. If you set it permanently it will be stored in your `.Renviron` file, and that will be accessed by ggmap persistently across sessions.

Users should be aware that the API key, is a PRIVATE key - it uniquely identifies and authenticates you to Stadia Maps' services. If anyone gets your API key, they can use it to masquerade as you to Stadia Maps and potentially use services that you have enabled. While Stadia Maps requires you to opt in to additional usage-based billing, this also means that anyone who obtains your key can potentially incur charges on your behalf or steal the quota that you have already purchased. So be sure to not share your API key. To mitigate against users inadvertently sharing their keys, by default ggmap never displays a user's key in messages displayed to the console.

Users should also be aware that ggmap has no mechanism with which to safeguard the private key once registered with R. That is to say, once you register your API key, any function R will have access to it. As a consequence, ggmap will not know if another function, potentially from a compromised package, accesses the key and uploads it to a third party. For this reason, when using ggmap we recommend a heightened sense of security and self-awareness: only use trusted packages, do not save API keys in script files, routinely cycle keys (regenerate new keys and retire old ones), etc.

See Also

<https://docs.stadiamaps.com/authentication/>, <https://stadiamaps.com/pricing>, <https://client.stadiamaps.com/signup/>

Examples

```
# this sets your Stadia Maps API key for this session
# register_stadiamaps(key = "YOUR-API-KEY")

# this sets your Stadia Maps API key permanently
```

```
# register_stadiamaps(key = "YOUR-API-KEY", write = TRUE)

has_stadiamaps_key()
stadiamaps_key()
```

revgeocode

Reverse geocode

Description

Reverse geocodes (looks up the address of) a longitude/latitude location using the Google Geocoding API. Note: To use Google's Geocoding API, you must first enable the API in the Google Cloud Platform Console. See [register_google\(\)](#).

Usage

```
revgeocode(
  location,
  output = c("address", "all"),
  force = FALSE,
  urlonly = FALSE,
  override_limit = FALSE,
  ext = "com",
  inject = "",
  ...
)
```

Arguments

| | |
|----------------|--|
| location | a location in longitude/latitude format |
| output | "address" or "all" |
| force | force online query, even if cached (previously downloaded) |
| urlonly | return only the url? |
| override_limit | override the current query rate |
| ext | top level domain extension (e.g. "com", "co.nz") |
| inject | character string to add to the url |
| ... | ... |

Value

a character(1) address or a list (the parsed json output from Google)

Author(s)

David Kahle <david@kahle.io>

See Also

<https://developers.google.com/maps/documentation/geocoding/>

Examples

```
## Not run:  requires Google API key, see ?register_google

## basic usage
#####

( gc <- as.numeric(geocode("the white house")) )
revgeocode(gc)
str(revgeocode(gc, output = "all"), 3)

## End(Not run)
```

route

Grab a route from Google

Description

Route two locations: determine a sequence of steps (legs) between two locations using the Google Directions API. Note: To use Google's Directions API, you must first enable the API in the Google Cloud Platform Console. See [register_google\(\)](#).

Usage

```
route(
  from,
  to,
  mode = c("driving", "walking", "bicycling", "transit"),
  structure = c("legs", "route"),
  output = c("simple", "all"),
  alternatives = FALSE,
  units = "metric",
  urlonly = FALSE,
  override_limit = FALSE,
  ext = "com",
  inject = "",
  ...
)

routeQueryCheck()
```

Arguments

| | |
|----------------|--|
| from | vector of origin addresses |
| to | vector of destination addresses |
| mode | driving, bicycling, walking, or transit |
| structure | structure of output, "legs" or "route", see examples |
| output | amount of output ("simple" or "all") |
| alternatives | should more than one route be provided? |
| units | "metric" |
| urlonly | return only the url? |
| override_limit | override the current query count |
| ext | domain extension (e.g. "com", "co.nz") |
| inject | character string to add to the url |
| ... | ... |

Value

a data frame (output="simple") or all of the geocoded information (output="all")

Author(s)

David Kahle <david@kahle.io>

See Also

<https://developers.google.com/maps/documentation/directions/>, [trek\(\)](#), [legs2route\(\)](#), [geom_leg\(\)](#), [register_google\(\)](#)

Examples

```
## Not run:  requires Google API key, see ?register_google

## basic usage
#####

from <- "houston, texas"
to <- "waco, texas"

route(from, to, structure = "legs")
route(from, to, structure = "route")

route(from, to, alternatives = TRUE)

## comparison to trek
#####
(route_df <- route(from, to, structure = "route"))
(trek_df <- trek(from, to, structure = "route"))
```

```
qmap("college station, texas", zoom = 8) +
  geom_path(
    aes(x = lon, y = lat), colour = "red",
    size = 1.5, alpha = .5,
    data = route_df, lineend = "round"
  ) +
  geom_path(
    aes(x = lon, y = lat), colour = "blue",
    size = 1.5, alpha = .5,
    data = trek_df, lineend = "round"
  )

qmap("college station, texas", zoom = 6) +
  geom_path(
    aes(x = lon, y = lat), colour = "red", size = 1.5,
    data = route_df, lineend = "round"
  )

## End(Not run)
```

theme_inset

Make a ggplot2 inset theme.

Description

theme_inset is a ggplot2 theme geared towards making inset plots.

Usage

```
theme_inset(base_size = 12)
```

Arguments

base_size base size, not used.

Value

a ggplot2 theme (i.e., a list of class options).

Author(s)

David Kahle <david@kahle.io>

Examples

```
library(ggplot2)
## Not run:

n <- 50
df <- expand.grid(x = 1:n,y = 1:n)[sample(n^2,.5*n^2),]
qplot(x, y, data = df, geom = 'tile')
qplot(x, y, data = df, geom = 'tile') + theme_nothing()

qplot(1:10, 1:10) +
  annotation_custom(
    grob = ggplotGrob(qplot(1:10,1:10)),
    8, Inf, -Inf, 2
  )

qplot(1:10, 1:10) +
  annotation_custom(
    grob = ggplotGrob(qplot(1:10,1:10) + theme_nothing()),
    8, Inf, -Inf, 2
  )

qplot(1:10, 1:10) +
  annotation_custom(
    grob = ggplotGrob(qplot(1:10,1:10) + theme_inset()),
    8, Inf, -Inf, 2
  )

## End(Not run)
```

theme_nothing

Make a blank ggplot2 theme.

Description

theme_nothing simply strips all thematic element in ggplot2.

Usage

```
theme_nothing(base_size = 12, legend = FALSE)
```

Arguments

| | |
|-----------|--------------------------------|
| base_size | base size, not used. |
| legend | should the legend be included? |

Value

a ggplot2 theme (i.e., a list of class options).

Author(s)

David Kahle <david@kahle.io>

Examples

```
# no legend example
n <- 50
df <- expand.grid(x = 1:n, y = 1:n)[sample(n^2, .5*n^2),]
p <- ggplot(df, aes(x, y)) + geom_raster()
p
p + theme_nothing()
p + theme_nothing(legend = TRUE) # no difference
p +
  scale_x_continuous(expand = c(0,0)) +
  scale_y_continuous(expand = c(0,0)) +
  theme_nothing()

# legend example
df$class <- factor(sample(0:1, .5*n^2, replace = TRUE))
p <- ggplot(df, aes(x, y)) + geom_raster(aes(fill = class))
p
p + theme_nothing()
p + theme_nothing(legend = TRUE)

p <- p +
  scale_x_continuous(expand = c(0,0)) +
  scale_y_continuous(expand = c(0,0))
p
p + theme_nothing()
p + theme_nothing(legend = TRUE)
```

trek

Grab a trek from Google

Description

Sequence treks (latitude-longitude sequences following ordinary paths, e.g. roads) between two locations using the Google Directions API. Note: To use Google's Directions API, you must first enable the API in the Google Cloud Platform Console. See [register_google\(\)](#).

Usage

```
trek(  
  from,  
  to,  
  mode = c("driving", "walking", "bicycling", "transit"),  
  output = c("simple", "all"),  
  alternatives = FALSE,  
  units = "metric",  
  urlonly = FALSE,  
  override_limit = FALSE,  
  ext = "com",  
  inject = "",  
  ...  
)
```

Arguments

| | |
|----------------|---|
| from | name of origin addresses in a data frame |
| to | name of destination addresses in a data frame |
| mode | driving, bicycling, walking, or transit |
| output | amount of output ("simple" or "all") |
| alternatives | should more than one route be provided? |
| units | "metric" |
| urlonly | return only the url? |
| override_limit | override the current query count |
| ext | domain extension (e.g. "com", "co.nz") |
| inject | character string to add to the url |
| ... | ... |

Value

a tibble

Author(s)

David Kahle <david@kahle.io> with the key decoding algorithm due to Stack Overflow user akhmed

See Also

<https://developers.google.com/maps/documentation/directions/>, <https://stackoverflow.com/questions/30270011/gmap-route-finding-doesnt-stay-on-roads/>, [route\(\)](#), [routeQueryCheck\(\)](#), [register_google\(\)](#)

Examples

```
## Not run:  requires Google API key, see ?register_google

## basic usage
#####

from <- "houston, texas"
to <- "waco, texas"

(route_df <- route(from, to, structure = "route"))
(trek_df <- trek(from, to, structure = "route"))

qmap("college station, texas", zoom = 8) +
  geom_path(
    aes(x = lon, y = lat), colour = "red",
    size = 1.5, alpha = .5,
    data = route_df, lineend = "round"
  ) +
  geom_path(
    aes(x = lon, y = lat), colour = "blue",
    size = 1.5, alpha = .5,
    data = trek_df, lineend = "round"
  )

from <- "rice university houston texas"
to <- "1001 Bissonnet St, Houston, TX 77005"
trek_df <- trek(from, to)
qmap(lon, lat, data = trek_df, geom = "path", maptype = "terrain",
  color = I("red"), size = I(2), alpha = I(.5)
)

trek_df <- trek(from, to, mode = "walking")
qmap(lon, lat, data = trek_df, geom = "path", maptype = "terrain",
  color = I("red"), size = I(2), alpha = I(.5)
)

trek_df <- trek(from, to, mode = "transit")
qmap(lon, lat, data = trek_df, geom = "path", maptype = "terrain",
  color = I("red"), size = I(2), alpha = I(.5)
)

## neat faceting example
#####

from <- "houston, texas"; to <- "waco, texas"
trek_df <- trek(from, to, alternatives = TRUE)

qmap(lon, lat, data = trek_df, geom = "path",
```

```

    color = route, size = I(2), maptype = "terrain",
    alpha = I(.5)
  )

  qmplot(lon, lat, data = trek_df, geom = "path",
    color = route, size = I(2), maptype = "terrain",
    zoom = 8
  ) + facet_grid(. ~ route)

## End(Not run)

```

 wind

Wind data from Hurricane Ike

Description

Wind data from Hurricane Ike

Details

Powell, M. D., S. H. Houston, L. R. Amat, and N Morisseau-Leroy, 1998: The HRD real-time hurricane wind analysis system. *J. Wind Engineer. and Indust. Aerodyn.* 77&78, 53-64

Author(s)

Atlantic Oceanographic and Meteorological Laboratory (AOML), a division of the National Oceanic and Atmospheric Administration (NOAA)

References

https://www.aoml.noaa.gov/hrd/Storm_pages/ike2008/wind.html

 XY2LonLat

Convert a tile coordinate to a lon/lat coordinate

Description

Convert a tile coordinate to a lon/lat coordinate for a given zoom. Decimal tile coordinates are accepted.

Usage

```
XY2LonLat(X, Y, zoom, x = 0, y = 0, xpix = 255, ypix = 255)
```

Arguments

| | |
|------|--|
| X | horizontal map-tile coordinate (0 is map-left) |
| Y | vertical map-tile coordinate (0 is map-top) |
| zoom | zoom |
| x | within tile x (0 is tile-left) |
| y | within tile y (0 it tile-top) |
| xpix | width of tile in pixels |
| ypix | length of tile in pixels |

Value

a data frame with columns lon and lat (in degrees)

Author(s)

David Kahle <david@kahle.io>, based on RgoogleMaps::XY2LatLon() by Markus Loecher of Sense Networks <markus@sensenetworks.com>

See Also

https://wiki.openstreetmap.org/wiki/Slippy_map_tilenames

Examples

```
## Not run:
XY2LonLat(480, 845, zoom = 11)
XY2LonLat(0, 0, zoom = 1)
XY2LonLat(0, 0, 255, 255, zoom = 1)
XY2LonLat(0, 0, 255, 255, zoom = 1)

## End(Not run)
```

| | |
|------|---|
| zips | <i>Zip code data for the Greater Houston Metropolitan Area from the 2000 census</i> |
|------|---|

Description

Zip code data for the Greater Houston Metropolitan Area from the 2000 census

Author(s)

U.S. Census Bureau, Geography Division, Cartographic Products Management Branch

References

Downloaded from <http://www.census.gov/geo/www/cob/z52000.html> (now defunct).

Index

aes(), 8
annotation_custom(), 39

bb2bbox, 2
bb2bbox(), 4, 39
borders(), 9

calc_zoom, 4
clear_geocode_cache (geocode), 5
crime, 5

distQueryCheck (mapdist), 43

facet_grid(), 50
facet_wrap(), 50
fortify(), 8

geocode, 5
geocode(), 6, 12
geocode_cache (geocode), 5
geocodeQueryCheck (geocode), 5
geom_leg, 8
geom_leg(), 61
geom_path(), 40
geom_segment(), 9
get_cloudmademap, 10
get_cloudmademap(), 11
get_googlemap, 12
get_googlemap(), 12, 16
get_map, 15
get_map(), 15, 27, 28, 36, 37, 39, 48, 50
get_navermap, 17
get_navermap(), 19
get_openstreetmap, 19
get_openstreetmap(), 16, 19
get_stadiamap, 20
get_stadiamap(), 20
get_stamen_tile_download_fail_log
 (get_stamenmap), 23
get_stamenmap, 23
get_stamenmap(), 23

ggimage, 25
gglocator, 26
ggmap, 27
ggmap(), 12, 14, 16, 19–21, 24, 48
ggmap-defunct, 36
ggmap-package (ggmap), 27
ggmap_credentials (ggmap_options), 37
ggmap_hide_api_key (register_google), 55
ggmap_options, 37
ggmap_show_api_key (register_google), 55
ggmapplot, 36
ggplot(), 8
google_account (register_google), 55
google_client (register_google), 55
google_day_limit (register_google), 55
google_key (register_google), 55
google_second_limit (register_google),
 55
google_signature (register_google), 55
grid::arrow(), 9

hadley, 38
has_ggmap_option (ggmap_options), 37
has_ggmap_options (ggmap_options), 37
has_google_account (register_google), 55
has_google_client (register_google), 55
has_google_key (register_google), 55
has_google_signature (register_google),
 55
has_stadiamaps_key
 (register_stadiamaps), 57

inset, 38
inset_ggmap (inset_raster), 39
inset_ggmap(), 39
inset_raster, 39
inset_raster(), 39

layer(), 9
legs2route, 40

legs2route(), [61](#)
load_geocode_cache (geocode), [5](#)
load_geocode_cache(), [6](#)
LonLat2XY, [41](#)

make_bbox, [42](#)
make_bbox(), [4](#)
mapdist, [43](#)
mutate_geocode (geocode), [5](#)
mutate_geocode(), [6](#)

OSM_scale_lookup, [46](#)
OSM_scale_lookup(), [19](#)

print.ggmap, [47](#)
print.google_credentials
 (register_google), [55](#)

qmap, [48](#)
qmap(), [28](#), [37](#)
qmpplot, [49](#)
qmpplot(), [49](#)

register_google, [54](#)
register_google(), [5](#), [14](#), [37](#), [38](#), [43](#), [56](#),
 [59–61](#), [64](#), [65](#)
register_stadiamaps, [57](#)
register_stadiamaps(), [58](#)
retry_stamen_map_download
 (get_stamenmap), [23](#)
revgeocode, [59](#)
route, [60](#)
route(), [9](#), [40](#), [65](#)
routeQueryCheck (route), [60](#)
routeQueryCheck(), [65](#)

saveRDS(), [6](#)
scrub_key (register_google), [55](#)
set_ggmap_option (ggmap_options), [37](#)
showing_key (register_google), [55](#)
stadiamaps_key (register_stadiamaps), [57](#)

tempfile(), [11](#), [13](#), [16](#), [18](#), [20](#)
theme_inset, [62](#)
theme_nothing, [63](#)
trek, [64](#)
trek(), [61](#)

utils::download.file(), [20](#)

wind, [67](#)

write_geocode_cache (geocode), [5](#)
write_geocode_cache(), [6](#)

XY2LonLat, [67](#)

zips, [68](#)